

INVISIBLE DOORS ALU3
FIRE RATED INVISIBLE DOORS ALU3
WOOD DOORS A2B
WOOD FIRE RATED DOORS A2B



INNER DOOR FACTORY

EN1634/1-2014 + A1/2018
CERTIFIED EI1 EI2 EI
EU BUILDING PRODUCT NR 1983 CD 60
EN305/2011-2022

TECHNICAL DATA DOOR SET
PRODUCT FAMILY

ALU3 invisible door
WOODEN DOOR IN ALU FRAME

DOOR LEAF	NON - REBATED
thickness	39,75 mm (+- 0.5)
Frame wood type	solid beech A/B 40 mm W
filling	honeycomb/ thermodoor/ tubular board
Finishing plate	hdf 3.2 mm primer white
Standerd width mm	630/680/730/780/810/830/880/930/980/1030
Standerd height mm	2015/2115
direction	Reversible L/ R/ push/ pull
milling	opening invisible hinges
	opening lock- no opening handle
FRAME	alu
finishing	WAWA 60
dimensions	40 mm w x 30 mm d
milling	Invisible hinges
	lockplate
HARDWARE	
hinges	invisible 3 D adjustable hinges
quantity	2-3
adjustment	+2 mm H, +-1.5 mm W, +-3 mm D
color	matt chrome
gasket	self-adhesive
color	Alu grey
lock	Magnetic key
color	matt chrome
Fixation plate	4/6
GAP	
top	3 mm
bottom	4 mm
Flatness	EN 1530 /EN 952 /EN 1121
15 à 30°C/ 25 à 75 % RV	V2
Mechanical resistance class – M	EN 947 / EN 948 / EN 949/ EN 950 M1
Usage frequency - f	EN 1191 / EN 12046-2 / EN 12400 / EN 1935 F7
Building product	EN13501-2011/2022
	1983 CD 60

Onder voorbehoud van technische wijzigingen