

TECHNICAL SPECIFICATIONS OF THE DOOR SET

WALLDOOR

PRODUCT FAMILY

Wooden door within a wooden frame

DOORLEAF	NON REBATED
Thickness	39,75 mm (+- 0.5)
door frame	Solid beech wood A/B, 40 mm wide
Core panel	Honeycomb, solid insulating / tubular
finition	hdf 3.2 mm white primer
width standard mm	630/680/730/780/810/830/880/930/980/1030
Height standard mm	2000/2015/2115
Swing Direction	L/R reversible
Milling	Concealed hinges opening
	lock - no opening handle
FRAME	
Frame Depth	40 mm
Frame Width	68 mm
wood	Solid beech wood A/B
cut out	invisible hinges
	counterplate lock
Stopper	43 x 15 mm
HARDWARE	
hinges	Concealed hinges 3 d adjustable
quantity	2-3
color	Matte chrome
Hinge Adjustment	+2 mm H, +-1,5 mm W, +-3 mm D
Door Seal Strip	Self-adhesive
color	Grey aluminum
Lock	Magnetic with key
color	mat chromé
CLEARANCES	
Top	3 mm
Bottom	4 mm
FLATNESS STANDARDS	EN 1530 /EN 952 /EN 1121
15 à 30°C/ 25 à 75 % RV	V2
Mechanical resistance class	EN 947 / EN 948 / EN 949/ EN 950
-M	M1
Operating force - f	EN 1191 / EN 12046-2 / EN 12400 / EN 1935
	F7

A2B DOORS